



# EZYJamb Fire Rating Specifications

Single Swing Frames				
<i>Positive Pressure tested to UL 10C</i>				
Frame Type	Width	Height	Rating	Min. Wall Size
EZC - Classic Adjust	3' 4"	8' 0"	90	4-1/2"
SRC - Single Rabbet	4' 0"	10' 0"	90	4-1/2"
ISD - Inswing	PENDING TESTING			

Pair Frames				
<i>Positive Pressure tested to UL 10C</i>				
Frame Type	Width	Height	Rating	Min. Wall Size
EZC - Classic Adjust	6' 0"	8' 0"	90	4-1/2"
SRC - Single Rabbet	6' 0"	10' 0"	90	4-1/2"
ISD - Inswing	PENDING TESTING			

Hardware Approved for use				
Hardware Type	EZC	SRC	ISD	Rating
4-1/2" Hinges Emboss Prep.		✓		90
4-1/2" Hinges Full Mortise		✓		90
Surface Hinges - SS	✓	✓		90
Concealed Hinges	✓	✓		90
T-Strike Emboss Prep.	✓	✓		90
T Strike Full Mortise		✓		90
ASA Strike Emboss Prep.	✓	✓		90
ASA Strike - Full Mortise		✓		90
4-7/8" Full cutout electric strike		✓		90
Concealed Closer cutout smaller than 3-23/32" Wide X 21-7/8" Long		✓		90

All frames for compliance with the applicable requirements of the following criteria: NFPA 252 (2012) and UL 10C (2015) "Positive Pressure Fire Tests of Door Assemblies".

All frames can be used with steel stud, wood stud or masonry construction as long as the wall assembly is rated for 90 minutes. Fire Ratings do not apply to 1-3/8" Frames.

- Edge seals not required.
- All frames tested to positive pressure.

EZY\_FIRE\_RATING\_0716

ANOTHER PRODUCT FROM:



For Sales and Technical Enquiries, please contact Ezyjamb USA 1 888 Ezy Jamb

T: 1 888 399 5262 | F: 585.545.3010 | E: sales@ezyjamb.com | W: www.ezyjamb.com